### Yantai Linghua New Material Co., Ltd.

**Add:** C-021 Caiyun Building, No. 18 Changjiang Road, Yantai FTZ China **Tel:** + 86-535-6249343 **Fax:** +86-535-6249344

## **Technical Data Sheet ---L4152**

Polyester----based ETPU (Explanded Thermoplastic Polyurethane)

#### 1.Feathers:

Low weight, high resilience performance, and has super physical properties.

### 2.Applications

Shoe materials, track, children's toys, bicycle tires and other fields.

## 3.Properties

Properties	Standard	Unit	Value
Physical Properties			
Density	ASTM D792	g/cm	0.16
Size		mm	3-5
Mechanical Properties			
Rebounding	ISO8307	%	58
Compression set(50%6h,45°C)		%	10
Tensile Strength	ASTM D412	Мра	1.3
Elongation at Break	ASTM D412	%	170
Tear Strength	ASTM D624	KN/m	15
Yellow Resistance(24h)	ASTM D 1148	Grade	4.5

Note: The above values are shown as typical values should not be used as specifications.

**4.Package:** 25kg/bag.

#### **5.Processing Guide**

For optimum results, previous drying of the product during 3-4hous at 100-110 ℃ is available, in a hot air circulatory, vacuum or desiccant-air dryer.

# 6.Environmental & Healthy & Safety

Take MSDS for reference.